

BULLDUCK T.TTM WAX CONVERTERS TEXTILES

CANVAS FABRIC

APPLICATIONS

Bullduck T.T. has a Tearstop construction with Terylene/Cotton corespun threads woven throughout the fabric. These threads are woven in both the warp and weft directions to reinforce the tear and tensile qualities of this very strong canvas. The fabric is designed specifically for very large semi-trailer truck tarpaulins where extra strength is required.tents and campervan roofing and walling.

Roll Width	204cm
Roll Length	54 metres
Nominal Weight	535gsm +/-30gsm
Thickness	0.64mm
Base Fabric	Woven 50/50 Poly/Cotton Tearstop Weave 23.6 ends per cm. 15.3 picks per cm. Yarn Count 2/12 ECC x 2/12 ECC (2/10 Corespun tear threads)
Treatment	Water penetration resistance, UV stabilised & mildew resistant
Colours	Green, Blue, Olive, Red, Antelope, Grey, Dark Green, Beige, Black, Orange & Maroon
Maximum Shrinkage	Warp: 2%
Cone Test (AS 2001.2.18)	Pass
Breaking Force (AS 2001.2.3)	Warp: 2586N Weft: 1644N
Hydrostatic Force (AS 2001.2.17)	1000mm min
Tear Resistance (AS 2001.2.10)	Warp: 207N Weft: 125N





Warranty applies to applications only used for

Camper Trailers









Standard warranty

Ricky Richards (Sales) Pty. Ltd | ABN 18 000 946 725 Information contained in this brochure is accurate and based on the latest product information available at the time of printing. While Ricky Richards (Sales) P/L makes all efforts to provide accurate information, we maintain the right to make changes as necessary. rickyrichards.com.au JUNE 2018